

**ACDB 10- 20 kw**  
**1 phase**

General Data		DC Surge Arrester	
Model No.	HS-10 to 20 , 1 phase	Brand	Elmex
input	1	Model	SPPV1+1T2-320
Output	1	Item model number	SPPV1+1T2-320
maximum voltage	240 V	Additional Features	IEC 61643 - 11 Compliance
AC voltage	240 V	Included Components	Enclosure Material - Thermoplastic UL 94-V0
MCB rating	63 A , 10 KA	Number of SPD	1 nos.
Encloser		MCB	
Brand	Fibox	Brand	L&T
Material type	Polycarbonate/ABS	MCB	63 A
Degree of protection	IP 66/67	Breaking capacity	10 KA
Degree of resistance to impacts	IK 07	Number of pole	2
Dimention	180x 180x100mm	Capacity	Terminal capaity 35 sq. mm
Cable Input Entry	PG11	Ip Rating	Degree of protection IP20
Cable Output Gland	PG11	Operation temperature	5'C to 55 'C
Terminal block		Environment	
Size	16 Sqmm	Operation temperature	-20'C to +60'C
Make	Elmex	Humidity	99%
Material type	PCC	Altitude	2000M
insulation inflammability test	IEC-60997-7-6	Installation	Wall Mounting
US standerd	UL 1059		
Salt Mist tested -	Part XI of indian standerd IS 9000		

